

# RECON SCOUT IR

Know Before You Go®

## Working As A Team With Your Team

### Simultaneous Operation of Two Robots

Now your tactical team can operate two Recon Scout® IR mobile reconnaissance robots in the same environment at the same time.

With the new alternate-frequency Recon Scout IR robots, no longer will you have to choose which entry team will use the robot. Instead, you can now deploy two robots to simultaneously explore different sections of the same environment. This will not only cut your reconnaissance time in half, but will also allow you to clear two floors of a building at the same time.

Existing Recon Scout and Recon Scout IR robots and operator control units (OCU) operate on frequency B. When you purchase a second robot it will operate on frequency A. Your new robot and new OCU will be delivered to you carrying an "A" frequency stamp for quick identification.

Before you send in your team, send in your Recon Scouts.



Contact:  
To learn more about the Recon Scout, please visit [www.reconrobotics.com](http://www.reconrobotics.com) or phone Katie Sisco at 952-935-5515, ext. 113.

Recon Robotics  
7620 West 78th Street  
Edina, MN 55439  
Phone: 952-935-5515  
Fax: 952-935-5508

[sales@reconrobotics.com](mailto:sales@reconrobotics.com)  
[support@reconrobotics.com](mailto:support@reconrobotics.com)

**RECON ROBOTICS™**  
[www.reconrobotics.com](http://www.reconrobotics.com)

Recon Scout is a registered trademark of ReconRobotics Inc. Copyright © 2010. Within the United States, sale of the Recon Scout to non-Federal and non-military entities is limited to state and local police and firefighters eligible for licensing under 47 C.F.R. § 90.20(a)(1) of the FCC Rules, and security personnel in critical infrastructure Industries as defined in the FCC Rules, 47 C.F.R. § 90.7. Operation of this product by non-federal and non-military entities requires an FCC license. These FCC Rules do not apply to sales made outside the United States.

Performance	Mechanical Specifications	Image Sensor
Indoor range: 100 ft/30m	Length: 7.375in/187mm	Black and white
Outdoor range: 300 ft/91m	Shell Diameter: 1.5in/38mm	IR illumination: 25ft
Speed: 1 fps/0.3mps	Wheel Diameter: 3in/76mm	Field of view: 60 degrees
Drop shock resistance: 30 ft/9.1m	Self-Balancer Length: 4in/102mm	Framerate: 30 fps
Throw shock resistance: 120 ft/31.4m	Weight: 1.2lb/544g	